Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

- 1. (Previously Presented) The method according to claim 21, wherein the subsequent re-recording and retaining includes re-recording the reproduced information as a hologram in the same position on the optical recording medium as the predetermined position from which the information was reproduced.
 - 2-3. (Canceled)
- 4. (Currently Amended) A hologram retention method according to claim 1, wherein the subsequent re-recording and retaining includes <u>recording</u> position information representing a position in which information has been recorded.
- 5. (Previously Presented) A hologram retention method according to claim 1, wherein when re-recording the reproduced information as a hologram in the same position on the optical recording medium as the predetermined position from which the information was reproduced, the reproduced information is re-recorded and retained so as to cause an intensity of a reconstructed beam to have a value that can be detected.
- 6. (Currently Amended) A hologram retention method according to claim 1, wherein when re-recording the reproduced information as a hologram in the same position on the optical recording medium as the predetermined position from which the information was reproduced, the reproduced information is re-recorded and retained so as to eausewith a polarization state so that a polarization state of a reconstructed beam obtained from the re-recorded hologram to be is different from a polarization state of a reconstructed beam obtained from the hologram preceding the re-recording.

- 7. (Original) A hologram retention method according to claim 1, wherein the optical recording medium comprises a photorefractive material, a photochromic material or a polarization sensitive material.
- 8. (Original) A hologram retention method according to claim 1, wherein the optical recording medium comprises polyester having an azobenzene frame in its side chain.
- 9. (Previously Presented) The method according to claim 21, wherein the subsequent re-recording and retaining includes re-recording and retaining the reproduced information as a hologram in a position on the optical recording medium different from the predetermined position from which the information was reproduced.

10-11. (Canceled)

- 12. (Currently Amended) A hologram retention method according to claim 9, wherein the subsequent reproducing and retaining includes <u>recording</u> position information representing a position in which information has been recorded.
- 13. (Original) A hologram retention method according to claim 9, wherein the optical recording medium comprises a photorefractive material, a photochromic material or a polarization sensitive material.
- 14. (Original) A hologram retention method according to claim 9, wherein the optical recording medium comprises polyester having an azobenzene frame in its side chain.
- 15. (Withdrawn) The method according to claim 21, further comprising the steps of:

dividing information of a file unit in a signal beam into a plurality of blocks, and multiplexing the information in an optical recording medium as holograms of a plurality of pages every block;

reproducing the information of the file unit; and

subsequently re-recording and retaining the reproduced file so as to re-divide the reproduced file into a smaller number of blocks.

16. (Withdrawn) A hologram retention method according to claim 15, comprising the steps of:

applying a signal beam and a reference beam simultaneously to the optical recording medium while changing an angle formed by the signal beam and the reference beam, and thereby changing a recording angle; and

dividing information of a file unit in the signal beam into a plurality of blocks, and multiplexing the information in the optical recording medium as holograms of a plurality of pages every block.

17. (Withdrawn) A hologram retention method according to claim 15, comprising the steps of:

making an angle formed by the signal beam and the reference beam constant, applying a signal beam and a reference beam simultaneously to the optical recording medium while relatively moving at least one of the signal beam and the reference beam, and the optical recording medium, and thereby changing a recording position; and

dividing information of a file unit in the signal beam into a plurality of blocks, and multiplexing the information in the optical recording medium as holograms of a plurality of pages every block.

18. (Withdrawn) A hologram retention method according to claim 15, comprising the steps of:

making an angle formed by the signal beam and the reference beam constant, applying a signal beam and a reference beam simultaneously to the optical recording medium while changing a wavelength of the reference beam and the signal beam; and

dividing information of a file unit in the signal beam into a plurality of blocks, and multiplexing the information in the optical recording medium as holograms of a plurality of pages every block.

19. (Withdrawn) A hologram retention method according to claim 15, comprising the steps of:

making an angle formed by the signal beam and the reference beam constant, applying a signal beam and a reference beam simultaneously to the optical recording medium while changing a phase of the reference beam; and

dividing information of a file unit in the signal beam into a plurality of blocks, and multiplexing the information in the optical recording medium as holograms of a plurality of pages every block.

- 20. (Withdrawn) A hologram retention method according to claim 15, wherein when re-recording a reproduced file, position information representing a position in which the file has been re-recorded is also recorded.
- 21. (Currently Amended) A hologram retention method comprising the steps of: reproducing information recorded as a hologram in a predetermined position of an optical recording medium; and

subsequently re-recording and retaining the reproduced information,

wherein the subsequent re-recording and retaining is preformed when an intensity of a reconstructed beam has fallen decreased to a predetermined value or less.

22. (Currently Amended) A hologram retention method comprising the steps of: reproducing information recorded as a hologram in a predetermined position of an optical recording medium; and

subsequently re-recording and retaining the reproduced information,

— wherein the subsequent re-recording and retaining is preformed when the number of times of reproduction has exceeded a predetermined value.

- 23. (Previously Presented) The method according to claim 22, wherein the subsequent re-recording and retaining includes re-recording the reproduced information as a hologram in the same position on the optical recording medium as the predetermined position from which the information was reproduced.
- 24. (Previously Presented) The method according to claim 22, wherein the subsequent re-recording and retaining includes re-recording and retaining the reproduced information as a hologram in a position on the optical recording medium different from the predetermined position from which the information was reproduced.